

(a) K140GLF Slate Gray
(b) K140GXF / (c) K140GXC\* Slate Gray

(d) K140WLF White

(e) K140WXF / (f) K140WXC\* White

(g) K140GLP Slate Gray

(h) K140GXP Slate Gray

(i) K140WLP White

(j) K140WXP White

Engine Type Inline 3-Cylinder E-TEC G2 D.I. x Stroke - in (mm) 3.85 x 3.25 (98 x 82.6)

 Bore x Stroke - in (mm)
 3.85 x 3.25 (98 x 8)

 Displacement - cu in (L)
 114 (1.9)

**Engine Model** 

Gear Ratio 2.08:1

Full Throttle RPM Range 5000-6000 RPM

(a)(d) 422 (191) (b)(e) 433 (196))

Weight - Ibs (kg)
(c)(f)(h)(j) 408 (185)
(g)(i) 397 (180)

Starting Electric
Controls ICON II

Fuel Induction E-TEC Direct Injection with stratified low RPM combustion mode

Alternator Output\*\* Net Amps 14 idle / 22 wot

(a)(b)(d)(e) DPS Power Assist

Steering
(c)(f) Tie Bar/Remote
(g)(h)(i)(j) Remote

 Trim Method
 Power Trim & Tilt

 Trim Range
 -6° to 15°

Tilt Range 81°

**Shaft Length - in (mm)** (a)(d)(g)(i) 20 (508) (b)(c)(e)(f)(h)(j) 25 (635)

**Lubrication** Multi-Point Targeted Oiling

Oil Tank Capacity - gal (L) 1.9 (7.2)

Recommended OilXPS Marine XD100Recommended Fuel87 Octane

Warranty 5-Year Engine<sup>†</sup> / 5-Year Corrosion

100% Global
Emissions Compliant

EPA 2013 / CARB 3 STAR / European Union

Mounting Centers - in (mm) Minimum 26 (660)

 Color
 Over 400 Color Panel Options

 Steering Angle
 (a)(b)(d)(e) +/- 38°

 (a)(b)(x)(x)(b)(ii)(x) +/- 40°

Integrated Features Dual Axis Rigging / iTrim

- \* Corresponding Counter Rotation Model
- \*\* Current amp calculated at 13.5 V.
- † 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.



 $(c)(f)(g)(h)(i)(j) +/- 40^{\circ}$